



## SHACKLES ALLOY & WIDE BODY


YOKE® WIDE BODY SHACKLES	160
PWB® GRADE M SHACKLES	160
PWB® GRADE S SHACKLES	161-162

# Yoke® Wide Body Shackles

## ► Forged Alloy Wide Body Shackle

- Shackles are forged from alloy steel with alloy pin.
- Size and Working Load Limit permanently shown on each shackle.
- All Shackles come with a batch code that links the product to it's test certificate for traceability.
- 100% magnaflux crack detection during manufacturing.

**Applications:** Marine, agricultural and general industrial




Part No.	Size (mm)	Working Load Limit (tonnes)	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	G (mm)	H (mm)	K (mm)	R (mm)	W (mm)	N.W (kg)
41180	19	7	91	41	18	22	32	46	150	104	32	33	1.7
41181	26	12.5	118	54	23	29	41	61	194	140	35	44	3.8
41182	32	18	148	64	30	36	51	68	238	172	38	54	6.7
41183	38	30	176	80	35	45	64	89	289	216	45	60	12.5

# PWB® Grade M Shackles

## ► Grade M Screw Pin Shackles

- Large Dee with screw collar pin formation.
- Available in galvanised finish.
- Suitable for lifting purposes.

**Applications:** Marine, agricultural and general industrial  
**Australian Standard:** AS 2741





Part No.	Size (mm)	WLL (tonnes)	d (mm)	D (mm)	w (mm)	L (mm)	e (mm)
46268	10	0.5	10	13	19	38	25
46269	13	0.75	13	16	28	54	32
46270	16	1.5	16	20	32	63	38
46271	19	2.0	19	22	38	73	44
46272	22	3.0	22	25	44	83	51
46273	25	3.8	25	30	51	95	57

# PWB® Grade S Shackles

## ► Grade S Safety Pin Shackles

- Easy and effective way of providing a connection to chain, wire rope and other fittings.
- Fitted with bolt, nut and split pin.
- Supplied in a galvanised finish with yellow painted pin.
- Suitable for lifting purposes.

**Applications:** Marine, agricultural, lifting and general industrial  
**Australian Standard:** AS 2741





Size (mm)	WLL (tonnes)	d (mm)	D (mm)	w (mm)	L (mm)	B (mm)	e (mm)	Part No.
<b>Bow Type</b>								
13	2.0	13	16	21	48	33	33	41233
16	3.25	16	20	27	61	43	40	41234
19	4.75	19	22	32	72	51	48	41235
22	6.5	22	27	37	84	58	54	41236
25	8.5	25	30	43	95	68	60	41237
29	9.5	29	33	46	108	74	67	41238
32	12.0	32	36	52	119	83	76	41239
35	13.5	35	39	57	133	92	84	41240
38	17.0	38	42	60	146	98	92	41241
44	25.0	44	51	73	178	127	110	41755
51	35.0	51	57	82	197	146	127	41978
63	55.0	63	70	105	267	184	152	41979
76	85.0	76	83	127	330	200	165	41980
<b>Dee Type</b>								
13	2.0	13	16	21	41	-	33	41743
16	3.25	16	20	27	51	-	40	41744
19	4.75	19	22	32	60	-	48	41745
22	6.5	22	27	37	71	-	54	41746
25	8.5	25	30	43	81	-	60	41747
29	9.5	29	33	46	90	-	67	41748
32	12.0	32	36	52	100	-	76	41749
35	13.5	35	39	57	113	-	84	41750
38	17.0	38	42	60	124	-	92	41751
44	25.0	44	51	73	146	-	110	41981
51	35.0	51	57	82	171	-	127	41982
63	55.0	63	70	105	203	-	152	41983
76	85.0	76	83	127	229	-	165	41984

# PWB® Grade S Shackles

## ► Grade S Screw Pin Shackles

- Screw collar pin formation.
- Supplied in a galvanised finish with yellow painted pin.
- Suitable for lifting purposes.

**Applications:** Marine, agricultural, lifting and general industrial  
**Australian Standard:** AS 2741



Size (mm)	WLL (tonnes)	d (mm)	D (mm)	w (mm)	L (mm)	B (mm)	e (mm)	Part No.
<b>Bow Type</b>								
6	0.5	6	8	12	29	20	17	48071
8	0.75	8	10	13	31	21	21	48072
10	1.0	10	12	17	37	26	25	48073
11	1.5	11	14	18	43	29	27	48074
13	2.0	13	16	21	48	33	33	48075
16	3.25	16	20	27	61	43	40	48076
19	4.75	19	22	32	72	51	48	48077
22	6.5	22	27	37	84	58	54	48078
25	8.5	25	30	43	95	68	60	48079
29	9.5	29	33	46	108	74	67	48080
32	12.0	32	36	52	119	83	76	48081
35	13.5	35	39	57	133	92	84	48082
38	17.0	38	42	60	146	98	92	48083
44	25.0	44	51	73	178	127	110	41970
50	35.0	51	57	82	197	146	127	41971
63	55.0	63	70	105	267	184	152	41972
<b>Dee Type</b>								
6	0.5	6	8	12	22	-	17	48058
8	0.75	8	10	13	26	-	21	48059
10	1.0	10	12	17	32	-	25	48060
11	1.5	11	14	18	37	-	27	48061
13	2.0	13	16	21	41	-	33	48062
16	3.25	16	20	27	51	-	40	48063
19	4.75	19	22	32	60	-	48	48064
22	6.5	22	27	37	71	-	54	48065
25	8.5	25	30	43	81	-	60	48066
29	9.5	29	33	46	90	-	67	48067
32	12.0	32	36	52	100	-	76	48068
35	13.5	35	39	57	113	-	84	48069
38	17.0	38	42	60	124	-	92	48070
44	25.0	44	51	73	178	-	110	41974
50	35.0	51	57	82	197	-	127	41975
63	55.0	63	70	105	267	-	152	41976